IN THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application and includes the Article 34 amendments made to the claims.

1. (Currently Amended) An electrochemical device having an electrode plate assembly that comprises: (a) at least one first electrode; (b) at least one second electrode; and (c) a separator interposed between the first electrode and the second electrode,

wherein said electrode plate assembly includes a PTC device,

said first electrode (a) comprises a first current collector sheet having a conductive area and an insulating area and at least one first electrode mixture layer carried thereon,

said second electrode (b) comprises a second current collector sheet having a conductive area and an insulating area and at least one second electrode mixture layer carried thereon,

said electrode plate assembly is a layered-type electrode plate assembly obtained by layering said first electrode, said second electrode and said separator, and

the conductive area of said first current collector sheet is connected to a first terminal on a first side face of said layered-type electrode plate assembly, the conductive area of said second current collector sheet is connected to a second terminal on a second side face of said layered-type electrode plate assembly, the insulating area of said first current collector sheet is positioned on said second side face, and the insulating area of said second current collector sheet is positioned on said first side face.

- 2. (Canceled)
- 3. (Canceled)
- 4. (Canceled)

- 5. (Currently Amended) The electrochemical device in accordance with claim 3 or 4 1, wherein said PTC device is shaped like a sheet.
- 6. (Currently Amended) The electrochemical device in accordance with any of elaims 3 to 5 claim 1, wherein said PTC device is positioned on said first side face or said second side face.
- 7. (Currently Amended) The electrochemical device in accordance with elaim 3 to 5 claim 1, wherein said PTC device is positioned in parallel with said first electrode, said second electrode and said separator in said layered-type electrode plate assembly.
- 8. (Currently Amended) The electrochemical device in accordance with elaim 3 claim 1, wherein the insulating area of said first current collector sheet and the insulating area of said second current collector sheet are positioned on the side faces of said layered-type electrode plate assembly other than said first side face and said second side face.
- 9. (Currently Amended) The electrochemical device in accordance with elaim 3 claim 1, wherein said layered-type electrode plate assembly has a side face on which the insulating area of said first current collector sheet and/or the insulating area of said second current collector sheet are/is positioned, other than said first side face and said second side face.
- 10. (Currently Amended) The electrochemical device in accordance with elaim 3 claim 1, wherein said first side face and said second side face are positioned on opposite sides of said layered-type electrode plate assembly.
- 11. (Currently Amended) The electrochemical device in accordance with elaim 3 claim 1, wherein a first insulating material portion is provided between said first terminal and said first side face for insulating said first terminal from said second electrode, and a second insulating

material portion is provided between said second terminal and said second side face for insulating said second terminal from said first electrode.

- 12. (Currently Amended) The electrochemical device in accordance with <u>claim 1</u> or 2, wherein said electrode plate assembly is a wound-type electrode plate assembly obtained by layering and winding said first electrode, said second electrode and said separator.
- 13. (Original) The electrochemical device in accordance with claim 12, wherein the conductive area of said first current collector sheet is connected to a first terminal on a first bottom face of said wound-type electrode plate assembly, the conductive area of said second current collector sheet is connected to a second terminal on a second bottom face of said wound-type electrode plate assembly, the insulating area of said first current collector sheet is positioned on said second bottom face, and the insulating area of said second current collector sheet is positioned on said first bottom face.
- 14. (Currently Amended) The electrochemical device in accordance with claim 12 or 13, wherein said PTC device is shaped like a flat plate or a round plate.
- 15. (Currently Amended) The electrochemical device in accordance with any of claims claim 12 to 14, wherein said PTC device is positioned on said first bottom face or said second bottom face.
- 16. (Original) The electrochemical device in accordance with claim 12, wherein a first insulating material portion is provided between said first terminal and said first bottom face for insulating said first terminal from said second electrode, and a second insulating material portion is provided between said second terminal and said second bottom face for insulating said second terminal from said first electrode.